



vulcan® Editor 20

Key performance

- Suitable for high speed newspaper presses
- Positive feeding
- Excellent reboundability
- **Implements all benefits of Dynatech System:**
 - Better vibration absorption
 - Less gears streaking marks
 - Higher paper smash resistance
 - Blanket consistency and high performance

MAIN APPLICATION

Newspaper Coldset

Vulcan Editor 20 is available in 3-ply, (1,96 mm) thickness.



Standard



Vulcan Editor 20



The product at a glance

INK COMPATIBILITY	Hybrid
PRINTING SURFACE COLOUR	Dark Blue
THICKNESS (mm)	1,96 (no pack on request)
AVERAGE LOAD VALUE N/cm² @ 0,23 mm Indentation	250
SURFACE ROUGHNESS (Ra micron)	1,0
FEED FEATURES	Positive
ELONGATION (%)	<0,9
TENSILE STRENGTHS (N/mm)	>60
WATER & SOLVENT PROTECTION	Yes
NEW TECHNOLOGY	Dynatech
ADDITIONAL INFORMATION	
PRESS FEATURES	Suitable for high speed shaftless presses

**FOR ANY FURTHER DETAILS AND FOR A QUOTATION
PLEASE REFER TO YOUR SALES MANAGER
OR EMAIL US AT: printing@trelleborg.com**